



Boon Drum LED Pendant BONP Series

Features

Decorative cut metal cylinder pendant is suspended with a 9 ft. adjustable cable. Product can be used over receptions desks, restaurants, and in public spaces. Canopy mounts to a standard junction box (not included).

Construction

Stamped metal with die-cut. The canopy fits over a standard junction box. Power supply connections must be made inside the junction box (not included).

Finish

Painted white or black metal finish.

Diffuser

White acrylic edge-lit light panel.

Electrical

Input 120 VAC, 60 Hz.
Compatible with residential TRIAC and ELV dimming.

LED

Integrated LED module capable of producing:
36W = 3000 lumens
3000K (CCT). Rated for 50,000 Hrs., 90 CRI.

Certification


cETLus listed for damp locations.

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 year from date of purchase.

**Specifications and dimensions
subject to change without notice.**

LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		



Ordering Information:

Black	White	LED	Source Lumens	CCT	DIA.	H
BONP2032L30D1BK	BONP2032L30D1WH	36W	3000	3000K	20"	8-1/2"