ΛFX

Dayton LED Pendant DYP Series

Features

Transitional shaded pendant with satin nickel accent detail. Pendant has a satin nickel finish and includes a hard backed whitelinen shade with white acrylic bottom diffuser; open top and center lock up. Suspended with a 3 ft. adjustable rigid stem expandable up to 9 ft. Product can be used over receptions desks, restaurants, and in public spaces. Canopy mounts to a standard junction box (not included).

Construction

Gear plate is die-formed of 20-gauge steel. Trim ring is 22-gauge steel and finial is die cast aluminum. Power supply connections must be made inside a junction box (not included).

Finish

Pan is finished in lighting grade white baked gloss enamel paint. Trim ring and finial have an applied satin nickel finish with a clear lacquer topcoat.

Electrical

Input 120-277 VAC 60 HZ. Compatible with residential (TRIAC/ELV) and commercial (0-10V) dimmers. TRIAC and ELV dimming only at 120VAC.

LED

Integrated LED modules capable of producing: 24" - 35W = 3200 lumens 30" - 46W = 4400 lumens Adjustable Choice 3000K, 3500K, 4000K (CCT). Rated for 50,000 Hrs., 90 CRI.

Certification

cETLus listed for indoor damp locations *Title 24/JA8 Compliant

Options

Additional stems sold separately.

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 year from date of purchase.

Specifications and dimensions subject to change without notice.

Ordering Information:

Satin Nickel	LED	Lumens	Adjustable CCT	DIA.	н
*DYP2432LAJUDSN	35W	3200	3000K/3500K/4000K	24"	9"
DYP3044LAJUDSN	46W	4400	3000K/3500K/4000K	30"	12"

LOCATION	DATE
PREPARED BY	QUANTITY
COMMENTS	FIXTURE TYPE
CATALOG NUMBER	_





