### 7958D28 D28"H34"L8



We are dedicated to providing the finest quality crystal chandelier for our customers. Our master craftsmen and designer pride themselves on their attention to detail. prompt, efficient service is our priority. Enclosed, are detailed instructions on how to properly. install your chandelier. Please read all instructions carefully and thoroughly. If you have any questions please fell free to call our toll free CHANDELIER HOTLINE AT:



1-888-388-3390 (UL) C (BL) US





# WARNING!!!

# CONTENTS ARE FRAGILE HANDLE WITH CARE

The metal frame and crystal components of this chandelier are very delicate. Please exercise extreme caution during unpacking and installation.

# WARNING!!!

After passing the main electrical wire through the 10mm pipe and connecting the pipe to the main body top connector, place all remaining pieces as shown in numerical order and in the orientation denicted Refer to the parts list to avoid confusion between parts. The part numbers coincide.

### **CAUTION**

- 1. Rated 110-130V/60Hz, bulb 40W maximum
- Care should be taken to avoid damage to the surface of lighting and wire, wearing gloves is recommended when installing.
- 3. Connect black or red wire of the lighting to live wire and white or blue wire to neutral wire and double colored(or bare copper)wire to ground wire.
- 4. Never install lighting on damp ceiling, the room should be dry and well ventilated.
- 5. Keep lighting away from acid, alkali and other corrosive chemical or gas, clean the lighting with clean soft cloth only.
- 6. Installation must be carried out by qualified electrician only.
- 7. Disconnect the power before installing cleaning and replacing lighting.
- 8. Never cover the lighting when power is connected.
- 9. Firmness must be secured when installing ceiling tube, chain, pipe and other connecting parts.
  10. Care should be taken to avoid damage when installing glass parts.
- 11. All electrical components must be installed by a licensed electrician and in accordance with the National Electrical Code and the appropriate local electrical codes. Make sure that the electrical supply to the chandelier is turned off at the main fuse or circuit breaker before doing any installation.


7958D28 D28"H34"L8


### Crystal Dressing Instructions


When dressing the chandelier with the crystals please remember to wear either rubber or cotton gloves. So as to prevent any demage or sandging on the crystals.












NO.	Quantity
A	8 strings
В	40 strings
С	8 strings
D	8 strings
Е	5 strings
F	1 strings
G	8 strings
H	8 strings

7958D28 D28"H34"L8

# Crystal Dressing Diagram

When dressing the chandelier with the crystals please remember to wear either rubber or cotton gloves. So as to prevent any damage or smudging on the crystals.



Connect both ends of G with C Connect both ends of H with D

(09

7958D28 D28"H34"L8

### CANOPY PARTS LIST

ZA: Existing Electrical Box (not supplied)



ZB:Crossbar



ZC:Crossbar Screws x 2(not supplied)



ZD:Canopy lock



ZE:Canopy



ZF:Metal Ring



ZG:Chain



ZH:Ground Wire



ZI:Canopy Loop



ZJ:Electric Main



ZK: Junction Caps





7958D28 D28"H34"L8

### Frame Assembly Instructions

Please read all instructions carefully. Before you proceed to install, make sure that the power supply is tamed off and off until installation is complete. Please note that each part has been assigned a letter. Please proceed in alphabetical order.

- 1. Install (Cast Canopy)01 to the electric Box and wire properly.
- 2. Put (Bottom Lock) 27 loosen, take off (Base) 23, (Glass Plate) 24, (Small Plate) 26, and Put (Glass S-shape Arm) 18 fixed on (Round Metal Slice) 20, then connect the positive and negative wire with main wire. Put (Base) 23, (Glass Plate) 24, (Small Plate) 26 passed through
- 4. In order (Glass Plate) 14, (Crystal Drop Holder) 15 away
- 5. Dressing Crystal using Diagram provided.

(All thread) 25, and put (Bottom Lock) 27.

the end

 $(\mathbf{Z}\mathbf{J})$ 

### Fram Parts List





17-All thread





18-Glass S-shape Arm



24-Glass plate



19-Glass ring



25-All thread



20-Round Metal Slice





21-Set Screw




27-Bottom lock

#### CANOPY INSTALLATION INSTRUCTIONS

Please read all instructions carefully. Before you proceed to install, make sure that the power supply is tamed off and off until installation is complete. Please note that each part has been assigned a letter. Please proceed in alphabetical order.

- ZA. Junction Box (not supplied)
- ZB. Crossbar
- ZC. Crossbar Screws
- ZD. Canopy Loop
- ZE. Canopy
- ZF. Metal Ring
- ZG. Chain
- ZH. Ground Wire
- ZI. Canopy loop
- ZJ. Electric loop
- ZK. Junction Caps
- 1. Attach the Crossbar(ZB) to the Junction Box(ZA) using the two crossbar screws(ZC) which are not supplied and should already be in your box.
- 2. Slide the Metal Ring(ZF) back up over the canopy(ZE), pass the canopy loop(ZD) through canopy(ZE), connect with the threaded pipe underside of the crossbar.
- 3. Pass the electric loop(ZJ) and ground wire (ZH) through the chain(ZG), the Metal Ring(ZF), the canopy(ZE), the canopy loop(ZD) and the crossbar(ZB) until the end of the electric Loop(ZJ) reaches the junction box(ZA) where you can make the appropriate connections.
- 4. Be sure when connecting the wire use electrician approved junction caps (ZK).
- 5. Stow the excess wire in the junction box (ZA).
- 6. Raise the canopy (ZE).
- 7. Metal Ring(ZF), attach canopy(ZE) to ceiling, slide Metal Ring(ZF) over canopy loop(ZD) and hold the canopy(ZE).



7958D28 D28"H34"L8

## Fram Parts List



01-Cast Canopy



02-chain Connector





05-big pipe cover





07-Vase

08-big pipe cover



09-Vase



10-Straight Pipe



11-plated Cylinder Screw Connector



12-All thread

[] Sleeve cover

13-Sleeve cover



14-Glass plate



15-Crystal Drop Holder

