



INSTALLATION REQUIREMENTS:

Fan must be attached to a securely anchored electrical junction box capable of withstanding a load of at least 35 lbs.

ELECTRICAL REQUIREMENTS:

Requires a grounded electrical supply line of 120 volts AC, 60 Hz, 15 amp circuit.

MOTOR SPECS:

153 x 15 AC motor is designed for optimal performance with this fan.

$\textbf{HENRY}^{\text{\tiny{TM}}}$

FP8**519**** 22" Ceiling Fan

	Α	В
Fan w/4.5" downrod	14.33"	12.61″
Fan w/12" downrod	21.83″	20.11"
Fan w/18" downrod	27.83"	26.11"
Fan w/24" downrod	33.83"	32.11"
Fan w/36" downrod	45.83"	44.11"
Fan w/48" downrod	57.83"	56.11"
Fan w/60" downrod	69.83"	68.11″
Fan w/72" downrod	81.83″	80.11″

Available Finishes					
BL	Black with Black				

Airflow / Energy Efficiency Info (120V)							
Fan Speed	Max RPM	CFM	CFM / Watts	Amps	Watts		
High	343	1282	101	0.11	13		
Med	265	998	116	0.09	9		
Low	161	437	115	0.06	4		

Light Bulb Information (120V)							
Bulb Type	Watts	Watts QTY Lumens Amount Color Temp		CRI			
LED	18	1	1400	3000	90%		

CONTROL OPTIONS:

TR500 hand-held remote control is included. Push button remote control with variable fan speeds, infinite light levels and off button. No option control recommend.

LIGHTING OPTIONS:

One 18-watt LED included.

DOWNROD OPTIONS:

Fan comes with 1" dia. x 4.5" long downrod (DR1-45). Optional downrods available in 12",18", 24", 36", 48", 60", and 72" lengths. A downrod coupler is available for installations requiring a downrod longer than 72". Fan can be mounted on a sloped ceiling upto 27°. Most sloped ceiling installations require a downrod longer than the standard 4.5" downrod. Optional sloped ceiling ball kits (SCB1-52) are available for slope angles greater than 27° and up to 42°. Optional close-to-ceiling kit is available as well—sold separately. Call technical support for more information.

LOCATION USE:

Fan is rated for dry and damp locations.