

# 12V 3000K 100 Lumen LED Mini All-Purpose Recessed Light Centennial Brass

16140CBR30 (Centennial Brass)

Project Name: \_\_\_\_\_  
Location: \_\_\_\_\_  
Type: \_\_\_\_\_  
Qty: \_\_\_\_\_  
Comments: \_\_\_\_\_



## Certifications/Qualifications

Prop65	Yes
<a href="http://www.kichler.com/warranty">www.kichler.com/warranty</a>	

## Dimensions

Height	2.25"
Width	2.25"

## Electrical

Operating Voltage Range	9-15VAC/VDC
Voltage	12V

## Mounting/Installation

Connector	Yes
Lead Wire Length	72
Wire Connectors	Wire Nuts

## Photometrics

Color Rendering Index	80
Delivered Efficacy (Lumens/Watt)	70
Delivered Lumens	100
Kelvin Temperature	3000K

## Primary Lamping

Lamp Included	Integrated
Light Source	LED
Max or Nominal Watt	1.5W
# of Bulbs/LED Modules	1
Max Wattage/Range	1.5W
Volt-Amperes (VA)	4.90

## Product/Ordering Information

SKU	16140CBR30
Finish	Brass
UPC	783927554923

## Specifications

Diffuser Description	Tempered Glass
Material	STAINLESS STEEL

## Additional Finishes

 Centennial Brass

 Stainless Steel

### Kichler

7711 East Pleasant Valley Road Cleveland, Ohio 44131-8010  
Toll free: 866.558.5706 or kichler.com

### Notes:

- 1) Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.
- 2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.

**KICHLER**®