

# Mariposa® 6' Whirlpool Bath K-1257-RAW

#### **Features**

- Bask® heated surface creates spa-like relaxation with soothing warmth on your back, shoulders, and neck.
- Three heat settings allow you to customize the surface temperature.
- Single-speed whirlpool offers performance and value, with 5 fully adjustable jets.
- Hydromassage flow and direction can be controlled at each jet.
- Generous 6-foot length provides spacious bathing for up to two people.
- Integral apron.
- Integral flange helps prevent water from seeping behind wall and simplifies alcove installation.
- Textured bottom surface
- Right-hand drain.

### Material

Acrylic

# **Hydrotherapy**

Whirlpool

#### Installation

Three-wall alcove.

# **Additional Hydrotherapy Options**

- Soaking Bath 1259-RA
- Soaking Bath + Bask heated surface 1259-RAW
- BubbleMassage air bath 1257-GRA
- VibrAcoustic 1257-VBRA
- VibrAcoustic + Bask heated surface 1257-VBRAW
- Whirlpool 1257-RA
- Whirlpool + heater 1257-HR
- Whirlpool + Bask heated surface 1257-RAW

# **Recommended Products/Accessories**

K-1491 Bath/Whirlpool Pillow K-7166-AF Bath Drain K-9696 Whirlpool 6-Jet Trim Kit K-24916 Wireless Music Kit



# Codes/Standards

ASME A112.19.7/CSA B45.10 CSA B45.5/IAPMO Z124 ASTM E162 ASTM E662 UL 1795

KOHLER® Plastic Baths and Receptors Lifetime Limited Warranty KOHLER® Hydrotherapy Components Five-Year Limited Warranty

See website for detailed warranty information.

#### Available Colors/Finishes

Color tiles intended for reference only.

Color	Code	Description
	0	White
	96	Biscuit
	47	Almond
	NY	Dune
18.0	G9	Sandbar





# **Mariposa®** 6' Whirlpool Bath


K-1257-RAW

18' (457 mm)


10-1/4" (260 mm)


No change in measurements if connected with drain illustrated. (K-7166-AF)


Recommended Faucet Location



**Integral Flange Detail** 







# **Required Electrical Service**

One dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI). Outside North America. this device may be known as a Residual Current Device (RCD).

Pump, Heated Surface:

120 V, 15 A, 60 Hz

#### **Technical Information**

All product dimensions are nominal.

Three-wall alcove Installation:

Right Drain location:

Basin area, bottom: 50" x 24" (1270 mm x 610 mm) Basin area, top: 65" x 27" (1651 mm x 686 mm)

Weight: 116 lbs (52.6 kg) Minimum floor load: 41 lbs/ft<sup>2</sup> (200.2 kg/m<sup>2</sup>)

Water depth: 14" (356 mm) Water capacity: 72 gal (272.5 L)

Electrical component Pump: 120 V, 7 A, 60 Hz

Heated Surface: 120 V, 0.5 A, 60 Hz, 65 rating:

W

Pump speed: Single

Minimum flat for door: 2-1/8" (54 mm)

#### **Notes**

Measure your actual product for rough-in details. Install this product according to the installation instructions.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.

If installing a rim-mount faucet, make sure there is no interference above or below the deck before drilling any holes.



Kohler Co. reserves the right to make revisions without notice to product specifications. For the most current Specification Sheet, go to www.kohler.com. 9-7-2019 06:29 - US/CA

