

TIMBER | FANDELIGHT

61011DWBK

- Two tone Driftwood and matte Black finish on metal
- DC Motor 6-speed fan with reverse function
- White Tunable LED transitions from warm 2700K to Daylight White
- Wall remote included
- Connect to Wifi for smart enabled function



Job Name : _____
 Job Type : _____
 Quantity : _____
 Comments : _____



ACCESSORIES (Sold Separately)



FCT6000WT

Wall Control




FCT6100WT

*Sold Separately

PRODUCT DESCRIPTION

A modern configuration of rustic elements, this Fandelier features a Driftwood finish on ring supported by brackets and thin struts in a contrasting Black steel. Within this timber wheel is an inner Black ring that houses an LED downlight. This minimalist form, with its use of rustic color palette, evokes a strikingly sophisticated composition that complements a wider variety of design aesthetics both rustic and modern. Whether used in a bedroom, entry, or over your dining space, this Fandelier is far more refreshing than conventional ceiling fans and much cooler than a light alone.

- Always consult a qualified electrician before installing any lighting product
- Installation Requirements:
 Ceiling fan attaches to electrical junction box securely anchored and capable of withstanding at least 35 lbs



ITEM#	LAMPING	DIMENSIONS	LUMENS	RATED DEL	DIMMABLE	WEIGHT	BLADES	BLADE PTICH
61011	120V, 30W LED 2700-4000K	D31" X 23"H	3,420	2,220	Remote or Wifi	36.38 lb	(3) x ABS (Included)	12

Energy Information at High Speeds		
AIRFLOW CFM	AIRFLOW EFFICIENCY	ELECTRICITY USE
2600 CFM	95 CFM / W	27.3W

ENERGYGUIDE

Estimated
Yearly Energy Cost

\$6

\$3 | | | \$34

Cost Range of Similar Models (19" - 84")

• Based on 12 cents per kWh and 6.4 hours use per day
 • Your cost depends on rates and use
 • Energy Use: 27.3 Watts

All estimates based on typical use, excluding lights

Airflow

2600

Cubic Feet Per Minute

• The higher the airflow, the more air the fan will move
 • Airflow Efficiency: 95 Cubic Feet Per Minute Per Watt

fco.governmy

FINISHES OPTION

Driftwood / Black (DWBK)

MATERIAL

Steel, Aluminum, ABS

RATINGS

cETLus
 Damp Location



INCLUDES

- Wall Mountable Remote Control
- 1 x 8" Downrod

DOWNROD OPTIONS

- 18" (FRD0118BK)
- 24" (FRD0124BK)
- 30" (FRD0130BK)
- 36" (FRD0136BK)

ADDITIONAL

OPERATING TEMPERATURE:
 -20°C (-4°F), 40°C (104°F)



WESTERN DISTRIBUTION CENTER (HEADQUARTER)

253 NORTH VINELAND AVE | CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER

101 GARDNER PARK | PEACHTREE CITY, GA 30269

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com