# Models 5031/5531

#### Essence™

Swirl-way® Oval Whirlpools and Bathtub



#### Bathtub and Whirlpool Features \_\_\_\_\_

- 60" x 41-1/2" x 24" oval bathtub
- Sculpted armrests and lumbar backrest
- Two pillows
- Two-person tub
- Mansfield® Limited Ten Year Warranty
- Available in standard colors (white, almond, biscuit and bone) and premium colors (British khaki, sterling silver, black and ice gray)

### **Basic Whirlpool Features**

- Hydro-V back jet system
- Single speed pump
- 1-button electronic keypad
- Color match trim
- Dual air controls

### **Luxury Whirlpool Features**

- Hydro-V back jet system
- Variable speed pump
- 5-button electronic keypad with digital temperature readout
- Metal trim upgrades
- Chromotherapy system
- In-line heater



Model 5031LUX

## Options \_

#### Cable Drain Lift and Turn Drain

Model #	Description		Model #	Description	
SW1319	Standard Colors		PF1320	Polished Chrome	04410
SW1320	Polished Chrome		PF1321	Everbrass (PVD)	
SW1321	Everbrass (PVD)		PF1322	Brushed Nickel	
SW1322	Brushed Nickel	-	PF1323	Oil Rubbed Bronze	
SW1323	Oil Rubbed Bronze	•	SWA100	Rainbow Pillow	

### Whirlpool Options \_\_\_\_\_

#### **Metal Trim**

Model #	Description		Model #	Description	
SW1335	Chrome				
SW1336	Everbrass (PVD)	900	SWP151	In-line water heater	Section 1997
SW1337	Brushed Nickel				
SW1338	Oil Rubbed Bronze				






## **Specifications**

Model #	Description	Codes/Standards		
5531	60" X 41-1/2" X 24" Oval Bathtub			
5031BAS	60" X 41-1/2" X 24" Basic Whirlpool Package	U P C USPC Usp		
5031LUX	60" X 41-1/2" X 24" Luxury Whirlpool Package			

Specification Description		Specification	Description	
Material	Acrylic, fiberglass reinforced	Number of Jets	16	
Construction	Self-contained, pre-plumbed whirlpool bath, with heat-bent rigid PVC pipe, mounted on a pre-leveled base	Water Capacity	60 gal. (min.) / 75 gal. (max.)	
Pump Motor	Basic: 1.5 HP Single speed induction pump Luxury: 1.5 HP Variable speed induction pump	Floor Loading Weight	47 lbs. / sq. ft. (229 kg/m <sup>2</sup> )	
Electrical Requirements	Basic: One 120V, 20 Amp, GFCI dedicated circuit. Optional heater: separate 120V, 20 Amp, GFCI dedicated circuit. Luxury: Two separate 120V, 20 Amp, GFCI dedicated circuits.	Shipping Weight	whirlpool - 170 lbs. bathtub - 145 lbs.	
On/Off Control	Basic: 1-button electronic control pad Luxury: 5-button electronic control pad with digital readout showing temperature of water, speed of pump and time remaining in 20-minute cycle.	Warranty	Limited Ten Year	

#### **Technical Information**



These dimensions are nominal and subject to change without notice.

When tested for compliance to the requirements of ASME A112.19.7M for "Whirlpool Bath Appliances" and ANSI Z124.1.2M "American National Standard for Plastic Bathtub and Shower Units", the tested units are found to comply and are acceptable for listing under IAPMO R & T.

(1448 mm)

Certified for permanent electrical connection only.



