

# NL-410 / NL-411

## 4" Adjustable Stepped Baffle with Ring

### FEATURES

**Trim:** Precision spun 0.040 aluminum baffle with deep grooves to reduce aperture glare. Nonreflective painted finishes. Gimbal ring allows lamp to be mounted on top of the trim and adjustable up to 35°. Separate trim ring available in plastic or metal, may also be used with custom combination of ring finishes.

**Mounting:** Trim includes three trim clips that securely mount trim in housing.

### COMPATIBLE HOUSINGS

Compatible with Line Voltage and Low Voltage housings. See individual specification sheets for more information.

### LAMP

#### Line Voltage

50W 120V MR16 GU10 max. (NSL-401AT/10; NSLIC-401AT/10; NSLR-404AT/10)

20W 120V MR16 GU10 max. (NSEIC-407AT/20; NSERIC-407AT/20)

25W 120V MR16 GU10 max. (NFBIC-401AT/25A)

#### Low Voltage

**Important:** Do not use glass lens (provided) when already using lamp with glass cover

20W-75W 12V MR16 (NL-401 Series; NL-402 Series; NLIC-401 Series; NLIC-402 Series;

NLR-403 Series; NLR-404 Series; NLR-405 Series)

### LABELS AND LISTINGS

cULus Listed for Damp Location when used with compatible housing.




Type

Project

Catalog No.

Notes

### PRODUCT IMAGES AND DIMENSIONS



**NL-410**

White Adjustable Stepped Baffle  
with White Metal Ring



**NL-411B**

Black Adjustable Stepped Baffle  
with Black Metal Ring

## 4" Adjustable Stepped Baffle with Ring

Catalog No.

**NL-410** = White Adjustable Stepped Baffle with White Metal Ring

**NL-410BZ** = Bronze Adjustable Stepped Baffle with Bronze Metal Ring

**NL-410N** = Natural Metal Adjustable Stepped Baffle with Natural Metal Ring

**NL-410P** = White Phenolic Adjustable Stepped Baffle with White Plastic Ring

**NL-411** = Black Adjustable Stepped Baffle with White Metal Ring

**NL-411B** = Black Adjustable Stepped Baffle with Black Metal Ring

**NL-411P** = Black Phenolic Adjustable Stepped Baffle with White Plastic Ring

## Compatible Housings

### Line Voltage

Catalog No.

**NSL-401AT/10** = 4" AT Line Voltage MR16 GU10 New Construction Housing

**NSLIC-401AT/10** = 4" ICAT Line Voltage MR16 GU10 Double Wall Housing

**NSLR-404AT/10** = 4" AT Line Voltage MR16 GU10 Remodel Housing

**NFBIC-401AT/25A** = 4" Fire Rated Line Voltage MR16 GU10 Housing

**NSEIC-407AT/20** = 4" ICAT Line Voltage MR16 GU10 New Construction Housing

**NSERIC-407AT/20** = 4" ICAT Line Voltage MR16 GU10 Remodel Housing

### Low Voltage

Catalog No.

**NL-4010AT/20**

**NL-4010AT/37**

**NL-4010AT**

**NL-401/50/277AT**

**NL-401AT/1EL**

**NL-401AT/2EL**

**NL-401/75**

**NL-401/75/277**

**NL-401/75/1EL**

**NL-401/75/2EL**

**NL-402S/20**

**NL-402S/37**

**NL-402S**

**NL-402S/1EL**

**NLIC-4010SAT/20**

**NLIC-4010SAT/37**

**NLIC-4010SAT**

**NLIC-401AT/277V**

**NLIC-401AT/1EL**

**NLIC-401AT/2EL**

**NLIC-4020SAT/20**

**NLIC-4020SAT/37**

**NLIC-4020SAT**

**NLIC-402AT/1EL**

**NLR-403S/20**

**NLR-403S/37**

**NLR-403S**

**NLR-403S/1EL**

**NLR-4040AT/20**

**NLR-4040AT/37**

**NLR-4040AT**

**NLR-404/50/277**

**NLR-404AT/1EL**

**NLR-404AT/2EL**

**NLR-404/75**

**NLR-404/75/277**

**NLR-404/75/1EL**

**NLR-404/75/2EL**

**NLR-405AT/20**

**NLR-405AT/37**

**NLR-405AT**

Example: **NL-410** = White Adjustable Stepped Baffle with White Metal Ring