

NMT-48/24C2D1

24V Dimmable Class II Hardwire Magnetic Driver

Source: 120V Input / 24V Output
48W

Type

Project

Catalog No.

Notes

PRODUCT DESCRIPTION

24V enclosed dimmable driver to be used with Nora Lighting's 24 Volt systems requiring a Class II driver. Produces 48 watts and can be dimmed with low voltage magnetic dimmer. Includes a regulator to provide constant current and constant voltage.

FEATURES

- Fully dimmable with low voltage magnetic dimming
- Integral regulator for constant current and voltage
- Manual Reset Overload Protection for each Class II Circuit
- Indoor/Outdoor Enclosure Type 3R Enclosure
- Conduit Access Wiring Compartment
- Made in USA
- Meets Class II output limits
- 24 Volt DC Rated output
- Includes 10' Power Line Connector
- cULus Listed & CSA approved

ELECTRICAL

Input Voltage: 120V

Output Voltage: 24VDC, 2A max.

Wattage: 48W

Dimming: Magnetic Low Voltage

Regulator: Constant Current and Constant Voltage

COMPATIBLE NORA 12V SYSTEMS

LED Drivers are compatible with Nora Lighting's 24V systems

SERIES	DESCRIPTION
NUTP1	24V Standard Tape Light (Silicone Encapsulated)
NUTP3	24V RGB Color Changing Tape Light
NUTP5	24V Hy-Brite Tape Light
NUTP7	24V Standard Tape Light (Non-Encapsulated)
NUTP8	24V High Output Tape Light
NUTP9	24V Side-Lit Tape Light
NUTP10	24V CCT Color Changing Tape Light
NUTP11	24V RGBW Color Changing Tape Light
NUTP51	24V Continuous Hy-Brite Tape Light
NUTP71	24V Continuous Standard Tape Light
NUTP81	24V Continuous High Output Tape Light
NULB	24V Lightbar Silk SBC

OPTIONAL ACCESSORIES

NALTL-10: 10' Power Line Connector (included)

NALTL-30: 30' Power Line Connector


NATL-302W: Power Line Splitter, white cable. Splits power line connector into two separate connections.

LABELS AND LISTINGS

- Three Year Limited Warranty
- cULus Listed
- CSA approved



PRODUCT IMAGES & DIMENSIONS



NMT-48/24C2D1

24V Dimmable Class II Hardwire LED Driver
MLV dimming



NALTL-10 / NALTL-30

Power Line Connector (10' included)



NATL-302W

Power Line Splitter

24V Dimmable Class II Hardwire Magnetic Driver

Output Voltage / Wattage

NMT-48/24C2D1 = 24V Duput / 48W

Optional Accessories

Description

NALTL-10 = 10' Power Line Connector (included w/each driver)

NALTL-30 = 30' Power Line Connector

NATL-302W = Power Line Splitter, White

Example: **NMT-48/24C2D1** = 24V 48W Dimmable Class II Hardwire Magnetic Driver