Type Project Catalog No.

FEATURES

Trim: High grade albalite lens attached to metal trim. Lens can be easily removed by hand without tools from below the ceiling for relamping.

Mounting: Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86).

COMPATIBLE HOUSINGS

Compatible with line voltage housings. See individual specification sheets for more information.

LAMP

Line Voltage 25W A19 Maximum (NHIC-270AT; NHRIC-270AT) 40W A19 Maximum (NHIC-170AT; NHRIC-170AT) 60W A19 Max. (NH-260; NH-270; NHIC-17/100DW0A; NHR-260; NHR-270) Sloped Line Voltage 40W A19 Maximum (NHIC-926DW0AT; NHIC-9260AT; NHRIC-9260AT)

LABELS AND LISTINGS

 \cdot cULus Listed for Wet Location when used with compatible housing.





6" Albalite Lens with Metal Trim	Compatible Housings
Catalog No.	Catalog No.
NT-22 = Albalite Lens with White Metal Trim NT-22BZ = Albalite Lens with Bronze Metal Trim NT-22G = Albalite Lens with Gold Metal Trim NT-22N = Albalite Lens with Natural Metal Trim	NH-260 = Non-IC New Construction / 60W max NHR-260 = Non-IC Remodel / 60W max NHIC-17/100DWQA = IC Air-Tight Double Wall New Construction / 60W max NHIC-17QAT = IC Air-Tight New Construction / 40W max NHRC-17QAT = IC Air-Tight Remodel / 40W max NH-270 = Shallow Non-IC New Construction / 60W max NHR-270 = Shallow Non-IC Remodel / 60W max NHIC-27QAT = Shallow IC Air-Tight New Construction / 25W max NHIC-27QAT = Shallow IC Air-Tight New Construction / 25W max NHRC-27QAT = Shallow IC Air-Tight New Construction / 40W max NHIC-27QAT = Shallow IC Air-Tight New Construction / 40W max NHIC-2826DWQAT = Sloped IC Air-Tight New Construction / 40W max NHIC-2926WQAT = Sloped IC Air-Tight Remodel / 40W max

Example: NT-22 = 6" Albalite Lens with White Metal Trim

NORA