

NT-30D / NT-33D

6" BR/PAR30 Metal Splay Trim

Type _____
 Project _____
 Catalog No. _____
 Notes _____

FEATURES

Trim: Metal splay trim with 3-7/8" open center.

Mounting: Trim includes two coil springs that clip and securely hold the trim into the housing when installed. Replacement coil springs are available (NRA-22).

COMPATIBLE LAMP / HOUSINGS

Line Voltage:

75W BR/PAR30 Maximum
 (NH-260; NH-270; NHIC-17/100DWQA; NHIC-17QAT; NHIC-27QAT; NHR-260; NHR-270; NHRIC-17QAT; NHRIC-27QAT)
 See individual housing specification sheets for more information.

LABELS AND LISTINGS

* cULus Listed for Damp Location when used with compatible housing



PRODUCT IMAGES & DIMENSIONS



NT-30D

3-7/8"

7-5/8"



NT-30DBZ



NT-30DCO



NT-30DNN



NT-33D

6" BR/PAR30 Metal Splay Trim

Catalog No.

- NT-30D** = 6" Metal Splay Trim, White
- NT-30DBZ** = 6" Metal Splay Trim, Bronze
- NT-30DCO** = 6" Metal Splay Trim, Copper
- NT-30DNN** = 6" Metal Splay Trim, Natural Metal
- NT-33D** = 6" Metal Splay Trim, Black

Compatible Housings

Line Voltage

- NH-260** = 6" Non-IC New Construction Housing
- NH-270** = 6" Non-IC Shallow New Construction Housing
- NHIC-17/100DWQA** = 6" IC Double Wall Air-Tight New Const. Housing
- NHIC-17QAT** = 6" IC Air-Tight Shallow New Construction Housing
- NHR-260** = 6" Non-IC Remodel Housing
- NHR-270** = 6" Non-IC Shallow Remodel Housing
- NHRIC-17QAT** = 6" IC Air-Tight Shallow Remodel Housing
- NHRIC-27QAT** = 6" IC Air-Tight Shallow Remodel Housing

Example: **NT-30D** = 6" BR/PAR30 Metal Splay Trim, White finish.