MIRIG European Style Haliam Project Source:: SOW MRIG GUID Catalog No. Item on the function of the functi	NTH-618		
(Lamp not Included) Idea Reduct Description Notes Une voltage die cast aluminum designer cube fixtures with MRIB light source. Yoke provides full adjustment of light source for special atiming and dual tightening knobs assure secure lock on angle position. PRODUCT IMAGES AND DIMENSIONS FETURES - Die cast atuminum provies superior strength and rigidity. - Log provide assthetic design. - Cost shuft included with fixture. - Lober shield included with fixture. - Log of the cust atuminum construction: cubical appearance and design features. All edges are softened for aesthetic appearance. Perforated spherical screen in rear functions as wire outlet and provides secure angle position - Die cast adjustion with the fight source and generative appearance of the fixture and provides secure angle position ELECTENCLA SYSTEM Socket: Porceliant twist and lock GUI0 socket Waitage: GUM arximum Socket: Porceliant wisting not lock GUI0 socket Waitage: GUM arximum - Joint of the second circuit of Nora Lighting NT-2300 series two-circuit track. DorTorbuck Circuit Conversion: Positive contact (opposite neutral and ground contacts) is preset to "down" position at factory but may be raised to the higher position to install onto the second circuit of Nora Lighting NT-2300 series two-circuit track. Die Alle Circuit Track. DPTIDAL ACCESSORIES NRH5 Filter (Blue, Clear, Frosted, Green, Linear, Pink, Red, Spread, Yellow) Labels AND LISTINGS			
PRODUCT DESCRIPTION Line voltage die cast aluminum designer cube fixtures with MRIB light source. Yoke provides full adjustment of light source for special animing and dual tightening knobs assure secure lock on angle position. FEATURES - Die cast aluminum provies superior strength and rigidity. - Low yrofile, aesthetic design. - Adjustable tycke for custom aming. - Clear shield included with fixture. - High-strength stainless stele electrical contacts. - One or two circuit track capable. CONSTRUCTION Mussing: G30 die-cast aluminum construction; cubical appearance and design features. All edges are softened for aesthetic appearance. Perforated spherical screen in rear functions as wire outlet and provides additional design benefit. Yoke: 0.0067: Rigid steel *wishbone" yoke connects fixture housing to electrical contact head. Single plastic angle tightening knobs maintain clean, decorative appearance of the fixture and provides secure angle position ELECTRICAL SYSTEM Socket: Porcelain twist and lock GUI0 socket Wattage: GVM waitum Lamp: MRI6 (not included) Ontor Included) Darber You Circuit Conversion: Positive contact (apposite neutral and ground contacts) is preset to "down" position at factory but may be raised to the higher position to install onto the second circuit of Nora Lighting NT-2300 series two-circuit track. Dor/Trowaic AccEssoneics Nu			
Line voltage die cast aluminum designer cube fixtures with MRIB flight source. Yoke provides full adjustment of light source for special aiming and dual tightening knobs assure secure lock on angle position. FFATURES - Ole cast aluminum provies superior strength and rigidity Low profile, aesthetic design Adjustable yoke for custom aiming Clear shield included with fixture High-strength stainless steel electrical contacts One or two circuit track capable. CONSTRUCTION Mususing: 030 die-cast aluminum construction: cubical appearance and design features. All edges are softened for aesthetic appearance. Perforated spherical screen in rear functions as wire outlet and provides additional design benefit. Yoke: 0.085' Rigid steel "wishbone" yoke connects fixture housing to electrical contact head. Single plastic angle tightening knobs maintain clean, decorative appearance of the fixture and provides secure angle position ELECTRICAL SYSTEM Socket: Porcelain twist and lock GUID socket Wattage: S0W maximum Lamp: RRI6 (not included) Dne/Two Circuit Conversion: Positive contact (opposite neutral and ground contacts) is preset to "down" position at factory but may be raised to the higher position to install onto the second circuit of Nora Lighting NT-2300 series two-circuit track. DPTIOWAL ACCESSORIES MH-100/RRI6: MRIB Filter (Blue, Clear, Frosted, Green, Linear, Pink, Red, Spread, Yellow) LABELS AND LISTINGS	(Lamp not Included)	Notes	
 Die cast aluminum provies superior strength and rigidity. Low profile, aesthetic design. Adjustable yoke for custom aiming. Clear shield included with fixture. High-strength stainless steel electrical contacts. One or two circuit track capable. CONSTRUCTION Roussing: 030 die-cast aluminum construction; cubical appearance and design features. All edges are softened for aesthetic appearance. Perforated spherical screen in rear functions as wire outlet and provides additional design benefit. Yoke: 0.085°, Rigid steel 'wishbone'' yoke connects fixture housing to electrical contact head. Single plastic angle tightening knobs maintain clean, decorative appearance of the fixture and provides secure angle position ELECTRICAL SYSTEH Socket: Porcelain twist and lock GUID socket Watage: 50W maximum Lamp: MRI6 (not included) One/Two Circuit Conversion: Positive contact (opposite neutral and ground contacts) is preset to "down" position at factory but may be raised to the higher position to install onto the second circuit of Nora Lighting NT-2300 series two-circuit track. OPTIONAL ACCESSORIES NH-DOZ/MRI6: MRI6 Filter (Blue, Clear, Frosted, Green, Linear, Pink, Red, Spread, Yellow) LABELS AND LISTINGS	ine voltage die cast aluminum designer cube fixtures with MR16 light source. Yoke provides full adjustment of light source for	PRODUCT IMAGES AND DIMENSIONS	
One/Two Circuit Conversion: Positive contact (opposite neutral and ground contacts) is preset to "down" position at factory but may be raised to the higher position to install onto the second circuit of Nora Lighting NT-2300 series two-circuit track. OPTIONAL ACCESSORIES NM-100/MR16: MR16 Filter (Blue, Clear, Frosted, Green, Linear, Pink, Red, Spread, Yellow) LABELS AND LISTINGS	 Die cast aluminum provies superior strength and rigidity. Low profile, aesthetic design. Adjustable yoke for custom aiming. Clear shield included with fixture. High-strength stainless steel electrical contacts. One or two circuit track capable ONSTRUCTION ousing: 030 die-cast aluminum construction; cubical appearance and design features. All edges are softened for aesthetic ap earance. Perforated spherical screen in rear functions as wire outlet and provides additional design benefit. oke: 0.085" Rigid steel "wishbone" yoke connects fixture housing to electrical contact head. Single plastic angle tightening kno naintain clean, decorative appearance of the fixture and provides secure angle position LECTRICAL SYSTEM ocket: Porcelain twist and lock GUI0 socket //attage: 50W maximum	ubs	
	ne/Two Circuit Conversion: Positive contact (opposite neutral and ground contacts) is preset to "down" position at factory b hay be raised to the higher position to install onto the second circuit of Nora Lighting NT-2300 series two-circuit track. PTIONAL ACCESSORIES IM-100/MR16: MR16 Filter (Blue, Clear, Frosted, Green, Linear, Pink, Red, Spread, Yellow)	but	

MR16 European Style Italia™

Catalog No.	Finish	Style
NTH-618	B = Black	(blank) = H-Style
	S = Silver	J = J-Style
	W = White	L = L-Style

Example: **NTH-618S** = MR16 European Style ItaliaTM, Silver Finish, H-Style Adapter

NORA