

NTM-513

5" BR30/PAR30 Air-Tight Baffle Cone with White Flange

Type

Project

Catalog No.

Notes

FEATURES

Trim: Precision spun 0.040 baffle with deep grooves to reduce aperture glare and white flange.

Mounting: Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86). Remove socket from socket plate within housing (if applicable), and mount directly onto trim.

COMPATIBLE HOUSINGS

Compatible with Line Voltage housings. See individual specification sheets for more information.

LAMP

Line Voltage

50W PAR30 (NHIC-5270AT; NHRIC-5270AT)

75W BR30/PAR30 (NH-5010; NHIC-5010AT; NHR-5040; NHRIC-5040AT; NFBIC-5INCATA)

GU24

13W-26W GU24 (NHIC-5G24ATFL)

LABELS AND LISTINGS

· cULus Listed for Damp Location when used with compatible housing




PRODUCT IMAGES AND DIMENSIONS



NTM-513B



NTM-513W



5" BR30/PAR30 Air-Tight Baffle Cone with White Flange

Catalog No.

NTM-513B = Black Air-Tight Aluminum Baffle Cone with White Flange

NTM-513W = White Air-Tight Aluminum Baffle Cone with White Flange

Compatible Housings

Line Voltage

Catalog No.

NH-5010 = 5" Non-IC New Construction Housing / 75W max

NHR-5040 = 5" Non-IC Remodel Housing / 75W max

NHIC-5010AT = 5" IC Air-Tight New Construction Housing / 75W max

NHRIC-5040AT = 5" IC Air-Tight Remodel Housing / 75W max

NHIC-5270AT = 5" IC Shallow Air-Tight New Construction Housing / 50W max

NHRIC-5270AT = 5" IC Shallow Air-Tight Remodel Housing / 50W max

NFBIC-5INCATA = 5" Line Voltage IC Air-Tight Fire Rated Housing / 75W max

GU24

Catalog No.

NHIC-5G24ATFL = 5" IC Air-Tight GU24 New Construction / 13W-26W max

Example: **NTM-513B** = Black Air-Tight Aluminum Baffle Cone with White Flange