


HIGH-CAPACITY WALL HEATERS MODELS 192, 194 & 198



Powerful and reliable for commercial uses yet good looking enough to blend with residential decors.

FEATURES

GRILLE:

- One-piece, heavy-duty 18 gauge steel with downflow louvers
- White, baked enamel
- Front-mounted thermostat
- Color coordinated thermostat knob
- Thermostat security cover – prohibits tampering

HEATER ASSEMBLY:

- Heating Element: Heavy-duty sheath element with steel-plate fins
- Thermostat: Snap-action heavy-duty disc-type
- Motor: Permanently lubricated (Models 192 & 194);
- Totally enclosed, permanently lubricated (Model 198)
- Thermal Overload: Manual reset protector
- Fan delay prevents cold air delivery as element heats up and provides warm air delivery as element cools down
- Operates on 240 VAC or 208 VAC
- Factory-wired wattages (easy field conversion to half-wattage): 2000W (Model 192); 3000W (Model 194); 4000W (Model 198).

HOUSING:

- Sturdy, 22 gauge steel construction finish with black, epoxy paint
- Mounts directly to wall studs in new or existing construction
- Furnished with a housing mask – prevents construction damage to roughed-in units
- Can be recess or surface mounted (surface mounting requires Model 85 Kit)

ACCESSORIES: (Purchase separately)

- Model 86W Line-Voltage Thermostat
- Model 85 Surface Mounting Kit
- Model 59W / 59V 60-Minute Timer (for use with Model 192 only)
- Model 61W / 61V 15-Minute Timer (for use with Model 192 only)

TYPICAL SPECIFICATION

Heater shall be Broan Model 192 (Model 194), (Model 198).

Unit shall have steel housing finished with black, epoxy paint. It will recess (surface) - mounted.

Heater to deliver 2000 watts (Model 192), 3000 watts (Model 194), 4000 watts (Model 198) of fan-forced heat. It must be field-convertible to operate at half-wattage. Heater shall include a manual reset thermal overload protector (and a fan delay). Motor to be permanently lubricated.

Grille will be White in color and made from 18 gauge steel. Unit to be controlled with front-mounted thermostat, Broan Model 86W. A security cover shall be provided so tamper-proof operation can be permitted.

Heater shall be U.L. Listed.



Broan-NuTone LLC Hartford, Wisconsin www.broan.com 800-558-1711

| REFERENCE | QTY. | REMARKS | Project |
|-----------|------|---------|-------------------|
| | | | Location |
| | | | Architect |
| | | | Engineer |
| | | | Contractor |
| | | | Submitted by Date |

PERFORMANCE RATINGS – HIGH-CAPACITY WALL HEATERS

| MODEL | WATTS | VOLTS | AMPS | BTU/HR | GRILLE | ELEMENT | FAN DELAY | SHIPPING WT. (lbs.) |
|-------|-----------------------------------|-------------------|---------------------------------|-------------------------------------|--------|--------------------------------|-----------|---------------------|
| 192 | 2000 / 1000 1500 / 750 | 240 208 | 8.3 / 4.1 7.2 / 3.6 | 6827 / 3413 5120 / 2560 | White | Steel-Sheathed Plate Finned | Yes | 23.0 |
| 194 | 3000 / 1500 2250 / 1125 | 240 208 | 12.5 / 6.2 10.8 / 5.4 | 10240 / 5120 7680 / 3840 | White | Steel-Sheathed Plate Finned | Yes | 23.0 |
| 198 | 4000 / 2000 3000 / 1500 | 240 208 | 16.7 / 8.3 14.4 / 7.2 | 13653 / 6827 10240 / 5120 | White | Steel-Sheathed Plate Finned | Yes | 23.0 |

BOLD ratings are factory-wired

