

**ALTAIR Ceiling Mount**  
**3-333-xx**

oxygen

FIXTURE TYPE \_\_\_\_\_

LOCATION \_\_\_\_\_

PROJECT \_\_\_\_\_

DATE \_\_\_\_\_



-24 Satin Nickel



-6 White



-15 Black



-22 Oiled Bronze

**LIGHT SOURCE** 1 x 13.5W LED with Driver on board, 3000K, CRI 90

**LUMINAIRE POWER** 13W at 120V

**RATED LIFE** 30000 hr RL

**OPTIONAL COLOR TEMPERATURES** 3000K Only

**LUMEN OUTPUT** Delivered: 800 lm (LM-79)

**INPUT VOLTAGE** 120V AC, 60Hz

**DRIVER OUTPUT** N/A

**DIMMING** TRIAC Dimming


**CONSTRUCTION** Cast Aluminum Housing with Steel Backplate

**DIFFUSER** - Etched White Glass

**FINISHES** White (-6), Black (-15),  
Oiled Bronze (-22), Satin Nickel (-24)

**MOUNTING** 4" Octagonal J-Box

**STANDARDS** ETL Damp listed, Conforms to UL STD 1598,  
Certified CAN/CSA STD C22.2 No 250.0.



**DIMENSIONS**

**W:** 7.00"

**L:** 7.00"

**H:** 1.00"

Order example for standard fixture:

**3-333-24** (x- Voltage - xxx-Sequence # - xx-Finish)

**3:** 120V Only

