

ONE-LIGHT FLUSH MOUNT

 Ceiling mounted • Damp location listed **PROGRESS LED**


P350055-009-30

Description:

A 12" domed, linen finish glass diffuser is discreetly supported from Brushed Nickel metal fittings and encloses an LED light source. 1,000 lumens 90+ CRI, 3000K.

Specifications:

- Brushed Nickel (-009) (plated)
- Steel Construction
- Etched White Linen glass diffuser
- Design features a domed, linen finish glass diffuser.
- Diffuser is discreetly supported from metal fittings encloses an energy-efficient light source
- 1600 source lumens 80 lumens/watt (source)
- 3000K color temperature, 90+ CRI.
- This fixture is not dimmable.
- Fixture covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- ENERGY STAR® qualified

Performance:

| | |
|------------------------|---|
| Number of Modules | 1 |
| Input Power | 20w |
| Input Voltage | 120 V |
| Input Frequency | 60 Hz |
| Lumens/LPW (Source) | 1600/80 (LM-82) |
| Lumens/LPW (Delivered) | 1000/50 (LM-79) |
| CCT | 3000 K |
| CRI | 90+ |
| Life (hours) | (L70/TM-21) |
| FCC | FCC Title 47, Part 15, Class B |
| Min. Start Temp | -30 °C |
| Max. Operating Temp | 30 °C |
| Warranty | 5 year warranty |
| Labels | cETLus Damp location listed ENERGY STAR® qualified |

Images:



Dimensions:

Diameter: 12"
Height: 4-1/4"

Glass
Width: 11-3/4"
Height: 3"