

Kylo LED

 Cable Suspension Mounted • Damp Location Listed **PROGRESS LED**

Description:

Kylo LED Collection 6-Light Matte Black Frosted Glass LED Modern Pendant Hanging Light

Specifications:

- Frosted Acrylic Cylindrical
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" recessed outlet box: 11.75 in W., 11.75 in ht., 1.5 in depth
- Mounting backplate for outlet box included
- 120 in of wire supplied 10 feet

Performance:

| | |
|------------------------|---|
| Number of Modules | 6 |
| Input Power | 24 W |
| Input Voltage | 120 V |
| Input Frequency | 60 Hz |
| Lumens/LPW (Delivered) | 1,790/77 (LM-79) |
| CCT | 3000 K |
| CRI | 90 CRI |
| Life (hours) | 50000 (L70/TM-21) |
| EMI/RFI | FCC Title 47, Part 15, Class B |
| Warranty | 5-year Limited Warranty |
| Labels | cETLus Damp Location Listed Meets California Title 24 JA8-2019 |

P500322-031-30



Dimensions:

Length: 11-3/4 in
 Height: 13 in
 Overall Ht. W/Cables: 132-5/8 in

Frosted Acrylic Cylindrical
 Width: 1-1/4 in
 Height: 7 in

P500322-031-30

Dimming Notes:

P500322-031-30 is designed to be compatible with many ELV controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls:

Lutron_DVELV-300P

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.