


# SPEAKMAN® SM-5040

## SentinelPro™ Thermostatic/Pressure Balance Shower System

### FEATURES:

- SentinelPro shower system includes SentinelPro concealed anti-scald thermostatic/pressure balance shower/bath valve & combinations.
- Chrome plated Brass wall plate with metal index.
- Chrome plated metal lever handle.
- Adjustable temperature limit stop (TLS). Factory set @ 110 F°.
- Brass body with integral spring check stops.
- Dual function thermostatic/pressure balance cartridge.
- Can be installed back-to-back. Includes rough-in template.
- Four port valve with ½ in. female Copper sweat and ½ in. NPT male inlets and outlets.
- Furnished with ½ in. cap.
- Chrome plated Brass supply ell with wall flange.
- 69 in. square lock stainless steel hose with rubber liner.
- Swivel connector. In-line vacuum breaker.
- 30 in. chrome plated Brass slide bar with mounting screws.
- VS-100-PC handshower with flow control device reduces flow to 2.5 gpm (9.5 L/min) maximum.
- Valve construction is Forged Brass Body and Brass Bonnet.
- Maximum capacity is 4.3 gpm +/- .2 @ 45 psi.
- Maximum Hot Water Supply Temperature is 185°F.
- Minimum Hot Water Supply Temperature is 5°F above set point.
- Maximum operating temperature is 120°F.
- Valve Temperature Set Point is 110°F (Based on 115-120°F hot & 55-65°F Cold).
- Maximum Static Pressure is 125 psi.
- Minimum flow (for +/-3°F performance) meets ASSE 1016 to 1.5 gpm (5.7 L/min).



### FINISH:



PC

### COMPLIANCE:

- ASSE 1016 & ASME 112.18.1/CSA B125.1 standards (SM-5000 Combo)

### OPTION:

Add suffix to model #

- VS-2272-E15 1.5 gpm hand shower & VS-156 pause/trickle adaptor  -E15
- 69 in. white vinyl hose  -VH
- Contractor packs available

### WARRANTY:

- 5 year limited

NOTE: 1. All dimensions are in inches (millimeters) unless otherwise specified and are subject to change without notice. 2. Unless otherwise specified all inlets and outlets are 1/2" female copper sweat and 1/2" male NPT. 3. The locations of the slide bar and supply ell are optional but restricted by the 69" hose length running from the supply ell connection to the hand shower (hand shower adjusted to highest position). 4. For ADA mounting locations consult ADAAG, ANSI A117.1, or state regulations.

## DIMENSIONS:

