

Beautiful for its simplicity, Cirque indoor or outdoor LED light fixture features a thick, round, pressed-glass shade with polished surface suspended from a die-cast base. The fixture has a sleek, modern design and offers installation versatility as a flush mount on the ceiling or as a sconce on the wall.

High quality LM80-tested LEDs

for consistent long-life performance and color

Outstanding protection against the elements:

- Marine-grade powder coat finishes
- · Stainless Steel mounting hardware
- Impact-resistant, UV stabilized frosted acrylic lensing

Ceiling or wall mounting option

SPECIFICATIONS

DELIVERED LUMENS	1143 LED		
WATTS	22.1 LED		
VOLTAGE	120V, 277V (LED Only)		
DIMMING	ELV		
LIGHT DISTRIBUTION	Symmetric		
MOUNTING OPTIONS	Wall or Ceiling		
ССТ	3000K or 4000K		
CRI	90+		
COLOR BINNING	3 Step		
BUG RATING	B1-U3-G1		
DARK SKY	Compliant (Ceiling)		
WET LISTED	IP65		
GENERAL LISTING	ETL		
CALIFORNIA TITLE 24	Can be used to comply with CEC 2016 Title 24 Part 6 for outdoor use. Registration with CEC Appliance Database not required.		
START TEMP	-30°C		
FIELD SERVICEABLE LED	No		
CONSTRUCTION	Aluminum		
HARDWARE	Stainless Steel		
FINISH	Marine Grade Powder Coat		
LED LIFETIME	L70; 70,000 Hours		
WARRANTY*	5 Years		

^{*} Visit techlighting.com for specific warranty limitations and details.



CIRQUE LARGE shown in bronze



CIRQUE LARGE shown in charcoal




ORDERING INFORMATION

7000	WCQ	SHAPE	CRI/CCT	FINISH	VOLTAGE
120V (ONLY	L LARGE - 11"	930 90 CRI, 3000K 940 90 CRI, 4000K INC INCANDESCENT	Z BRONZE H CHARCOAL	120 120V 277 277V

CIRQUE LARGE WALL/CEILING






Cirque Large

PHOTOMETRICS*

*For latest photometrics, please visit www. techlighting.com/OUTDOOR

CIRQUE LARGE

Total Lumen Output: 1143
Total Power: 22.1
Luminaire Efficacy: 51.5
Color Temp: 3000K
CRI: 90+
BUG Rating: B1-U3-G1



PROJECT INFO

FIXTURE TYPE & QUANTITY JOB NAME & INFO NOTES



GENERATION BRANDS 7400 Linder Avenue, Skokie, Illinois 60077 T 847.410.4400 F 847.410.4500