

# 3.5" OCULUX - Open Reflector

R3BRD, R3BSD

# WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project: \_\_\_\_\_

Location: \_\_\_\_\_

## PRODUCT DESCRIPTION

Designed to fit in tight plenum space

## FEATURES

- Energy Star® Rated
- Title 24 Compliant
- IC-rated Remodel and New Construction
- Airtight in New Construction and remodel
- Shallow housing under 4" depth
- Cutout 4 1/4"
- Single spot light source

## SPECIFICATIONS

**Construction:** Die-cast aluminum trim and heat sink; polycarbonate trim for Dead Front

**Dimming:** ELV or TRIAC or 0-10V dimming compatible

**Input:** 120V for R3BNICA-10, R3BBRT-10; 120-277V for R3BNICA-10U

**Power:** 11W

**Mounting:** Retention clips firmly hold trim to housing.

**Finish:** Powder coated

**Ceiling thickness:** 1/2" - 1"

**Standards:** ETL&cETL, Wet location listed

Trims (Order Housing Separately)	Model	Beam	Max Lumens	Max CBCP	Color Temp	Finish
	<b>R3BRD</b> Round Open Reflector Wet Location Listed 40° visual cutoff	<b>S</b> 15° <b>N</b> 25° <b>F</b> 50°	970	5132	<b>927</b> 2700K <b>930</b> 3000K	<b>HZWT</b> Haze/White <b>BN</b> Brushed Nickel <b>WT</b> White
	<b>R3BRDP</b> Dead Front* Open Reflector Wet Location Listed 40° visual cutoff	<b>N</b> 25°	1025	2985	<b>927</b> 2700K <b>930</b> 3000K	<b>WT</b> White
*Conforms to local code Dead Front requirements						
	<b>R3BSD</b> Square Open Reflector Wet Location Listed 35° visual cutoff	<b>S</b> 15° <b>N</b> 25° <b>F</b> 50°	930	4710	<b>927</b> 2700K <b>930</b> 3000K	<b>HZWT</b> Haze/White <b>BN</b> Brushed Nickel <b>WT</b> White

**R3BRD-** \_\_\_\_\_ - \_\_\_\_\_ - \_\_\_\_\_

Example: **R3BRD-S930-BN**

wacighting.com  
 Phone (800) 526.2588  
 Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
 44 Harbor Park Drive  
 Port Washington, NY 11050

Central Distribution Center  
 1600 Distribution Ct  
 Lithia Springs, GA 30122

Western Distribution Center  
 1750 Archibald Avenue  
 Ontario, CA 91760







# 3.5" OCULUX - Open Reflector

R3BRD, R3BSD

# WAC LIGHTING

Responsible Lighting®

Housings (Required) - Order separately from trims

	Model	Input	Dimming	Notes
<p><i>New Construction</i></p>  <p>14½" min 24½" max</p> 	<b>R3BNICA-10</b> IC-Rated, Airtight	120V	100% - 5% TRIAC, ELV, 0-10V	Less than 4" plenum depth  Allows adjustment in any direction when used with adjustable trims
	<b>R3BNICA-10U</b> IC-Rated, Airtight	120V - 277V	<b>120V</b> 100% - 5% TRIAC, ELV, 0-10V  <b>277V</b> 100% - 1% 0-10V	Ceiling thickness: ½" - 1"
<p><i>New Construction</i> 2 Hour Fire Rated</p>  <p>14½" min 24½" max</p> 	<b>R3BNICAF-10</b> IC-Rated, Airtight, Fire Rated	120V	100% - 5% TRIAC, ELV, 0-10V	Double sheet metal housing Supports two layer fire rated drywall ANSI / UL 263 Fire Rated Allows adjustment in any direction when used with adjustable trims Ceiling thickness: ½" - 1"
<p><i>Remodel</i></p>  <p>2 1/16"</p> 	<b>R3BBRT-10</b> IC Rated	120V	100% - 5% TRIAC, ELV, 0-10V	Allows adjustment in any direction when used with adjustable trims Ceiling thickness: ½" - 1"

Example: **R3BNICAF-10**

wacighting.com  
Phone (800) 526.2588  
Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
44 Harbor Park Drive  
Port Washington, NY 11050

Central Distribution Center  
1600 Distribution Ct  
Lithia Springs, GA 30122

Western Distribution Center  
1750 Archibald Avenue  
Ontario, CA 91760