RUBIX - model: WS-W25

LED Wall Mount

WAC LIGHTING

Responsible Lighting®

			_					
		Fixture Type	e:					
		Catalog Nui	mber	:				
		Project:	Project:					
		Location:						
PRODUCT DESCRIPTION	SPECIFIC	ATIONS						
Precise engineering using the latest energy efficient LED technology	,	Construction: Aluminum with etched glass.						
with a built-in reflector for superior optics; An appealing cylindrical		Power: Integral driver in luminaire. 120V - 277V input.						
profile with a powerful LED down light perfect for accent and wall w lighting.	Light Sou	Light Source: High output LED						
igricity.	Mountin	Mounting: Mounts directly to junction box						
	Dimming	Dimming: 0-10V Dimming: 100%-10%						
FEATURES		ELV Dimming: 100%	o-15% (120V on	ly)			
Mounts Up or Down	Finish: Br	Finish: Brushed Aluminum (AL), Black (BK), Bronze (BZ), Graphite (GH), White (WT)						
IP65 Rated, ETL & cETL Wet Location Listed	Color Ter	Color Temp: 3000K						
Die-Cast Aluminum Construction	CRI: 90	CRI: 90						
Universal Voltage Input (120V - 277V)	Rated Lif	Rated Life: 70,000 hours						
Dimming: ELV (120V) or 0-10V		Standards: IP65 Rated, ETL & cETL Wet Location Listed, Dark Sky Friendly,						
ADA Compliant	ADA Com	pliant						
Beam	Photometry	Voltage	Watt	Lumens	Finish			
10" 3%" WS-W2509 Single Light 5%" Dark Sky Friendly 86°		120V - 277V						

Single	e Light	10"		WS-W2509 5%" Dark Sky Friendly	ly ^{86°}	120V - 277V	16W	805			
Doubl	le Light	10"	37%"	WS-W2510 5%"	86°	120V - 277V	30W	1385	BK BZ GH	Brushed Aluminum Black Bronze Graphite White	
]-[

Example: WS-W2510-GH

WAC Lighting www.waclighting.com Phone (800) 526.2588 • Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive • Port Washington, NY 11050 Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center 1750 Archibald Avenue • Ontario, CA 91760 Phone (800) 526.2588 • Fax (800) 526.2585

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. SEP 2017